

IP 65

class I

IK07 2J xx5



BLIZ


design R. Fiorato - F. Pagliarini

Series of indoor or outdoor wall and ceiling mount luminaires, comprising:

- Aluminium body, trim, guard and screen
- Glass diffusers
- Stainless steel locking screws
- Hexagonal key supplied for external locking screws
- The Supervisa version is compliant with anti-light pollution regulations
- The twilight models (C) are equipped with sensors for automatic activation
- Suitable for resistive or inductive load
- Tripping threshold from 5 lux to daylight level

Wand- und Deckenleuchten für Innen- und Aussenbereiche, bestehend aus:

- Gehäuse, Zierring, Gitter und Blenden aus Aluminium
- Abdeckungen aus Glas
- Verschlusschrauben aus Edelstahl
- Sechskantschlüssel zur Befestigung der Außenschrauben im Lieferumfang
- Die Version Supervisa entspricht den Bestimmungen gegen Lichtsmog
- Die Dämmerungsversionen (/C) sind mit Sensor zum automatischen Einschalten versehen
- Sowohl für induktive als auch für ohmsche Ladung geeigneter Sensor
- regulierbare Interventionsschwelle von 5 lux bis 300 lux



IK07 2J xx5



E27
max 1x60W



E27
1x20W Dulux EL Longlife
1x23W Dulux EL Longlife



G24d-2
1x18W



G24q-1
1x13W

LAMPHOLDER	COLOUR CLASS	CLASS	COS φ	CODE	NOTES
FASSUNG W	ILCOS FARBE	KLASSE	≥ 0,9	BESTELLN.R.	BEMERKNG. EURO

BLIZ RING

E27	max 1x60w IAA	GR2	I •	700192	
E27	max 1x60w IAA	AN3	I •	700193	
E27	max 1x60w IAA	DB1	I •	700194	

BLIZ RING 230V - 50HZ

Fluorescent - magnetic ballast 230V 50Hz/Leuchtstofflampen - VVG 230V 50Hz

G24d-2	1x18w	FSQ	GR2	I •	≤B2	700356
G24d-2	1x18w	FSQ	AN3	I •	≤B2	700357
G24d-2	1x18w	FSQ	DB1	I •	≤B2	700358

BLIZ RING/C

Fluorescent - electronic ballast 220/240V 50/60Hz/Leuchtstofflampen - EVG 220/240V 50/60Hz

G24q-1	1x13w	FSQ	GR2	I	A2÷A3	700507
G24q-1	1x13w	FSQ	AN3	I	A2÷A3	700508
G24q-1	1x13w	FSQ	DB1	I	A2÷A3	700509

BLIZ RING 240V-50HZ

Fluorescent - magnetic ballast 230V 50Hz/Leuchtstofflampen - VVG 230V 50Hz

G24d-2	1x18w	FSQ	GR2	I	≤B2	700341
G24d-2	1x18w	FSQ	AN3	I	≤B2	700342
G24d-2	1x18w	FSQ	DB1	I	≤B2	700343

PACKAGE SIZE / VERPACKUNGSMABE

27 x 14,5 x 14 cm
(master x 6)

DISTANCE BETWEEN FIXING HOLES / BOHRLOCHABSTAND

